



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	136A
Cone Kit:	C8R2235
Nom. Impedance:	8 Ohm
Dynamic Test Input V:	10
Sweep Frequency Hz:	20-1200
D.C. Resistance Ohms:	5.8 min/6.8 max
Gap Gauge:	.057"
Notes:	Mass Ring
If Not Serviceable, Replace With:	2235H
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different. Replace both units in a stereo pair.
Additional Parts Currently Available*:	
Dome:	50201
Mounting Gasket:	34499
Trim Gasket:	52347
HIGH FREQUENCY DRIVER:	LE85
Diaphragm Kit:	D16R2421
Nom. Impedance:	16 Ohm
Dynamic Test Input V:	3.5

HIGH FREQUENCY DRIVER (Cont'd)

Sweep Frequency Hz:	550-1200
D.C. Resistance Ohms:	5.9 min/7.0 max
Gap Gauge:	.031"
Notes:	
If Not Serviceable, Replace With:	2425J
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different. Replace both units in a stereo pair.
Additional Parts Currently Available*:	
Horn:	H91 (Lens L91 No Longer Available)

SYSTEM SPECIFICATIONS:

Nom. Impedance:	8 Ohm
Power Capacity:	150 Watts Continuous Program
Crossover Frequency:	800 Hz
Sensitivity:	80dB (1 Watt @ 15 Feet)
Enclosure Dim:	32-3/4" x 23-7/8" x 21-1/4" D 83cm x 61cm x 54cm
Shipping Weight:	131 lbs. - 59.4 kg.
Additional Parts Currently Available*:	
Binding Posts:	Red: 10243 Black: 10244

*Other parts may also be available. Check with JBL for details.