



299-8A/299-16A Compression Driver Loudspeakers

Features

- 100 watt power capacity from 500 Hz (continuous program power)
200 watt power capacity from 500 Hz (peak power)
150 watt power capacity from 1000 Hz (continuous program power)
300 watt power capacity from 1000 Hz (peak power)
- Tangerine® radial phasing plug
- Pascalite™ diaphragm assembly
- Field replaceable diaphragm
- 8 Ω and 16 Ω minimum impedances
- Input screw terminals
- Low distortion
- High sensitivity

Benefits

- For use in sound systems at preferred crossover frequencies
- Improves extreme high frequency response
- Allows large acoustic power outputs while maintaining a wide bandwidth.
- Adjustable dowel pin centered, field replaceable
- Predictable loads when used singly or in multiples; more latitude in system designs.
- Positive connection for most types of wires and terminal lugs.
- More accurate speech and music reproduction.
- Greater efficiency

Advantages

- Provides excellent reliability and high performance
- Excellent fidelity for speech and music systems
- Reliability and high performance, long-life
- Easy serviceability
- Provides predictable loads to amplifiers above crossover frequency
- Quick and long term reliable connections
- Superior sound quality
- More acoustical output with less power amplifier requirements



**ALTEC
LANSING®**